

# USER'S MANUAL

**OCB-GT-06**

**GPS Personal Tracker**

**V6.3**

## Contents

1.Product Overview .....	- 3 -
2.For Your Safety .....	- 3 -
3.OCB-GT-06 Characteristics .....	- 4 -
4.Getting Started.....	- 4 -
4.1 Hardware and Accessories .....	- 4 -
4.2 View .....	- 5 -
4.3 Functional Parts.....	- 5 -
4.4 First Use .....	- 6 -
5. Change Password.....	- 7 -
6. Time Zone .....	- 7 -
7. Track.....	- 7 -
7.1 Track by SMS.....	- 7 -
7.2 Track by Calling.....	- 8 -
7.3 Track by Preset Interval.....	- 8 -
7.4 Google Earth and Google Map.....	- 8 -
7.5 Track by OCB-GPS-SERVER-01/OCB-GPS-SERVER-02 .....	- 9 -
7.6 Track by GPRS (Meiligao Protocol) between Server and Tracker .....	- 9 -
7.6.1 Set Tracker’s GPRS ID .....	- 9 -
7.6.2 Set APN .....	- 10 -
7.6.3 Set IP and Port .....	- 10 -
7.6.4 Set DNS Server IP (optional) .....	- 10 -
7.6.5 Enable GPRS Tracking .....	- 10 -
7.6.6 Set GPRS Interval .....	- 10 -
7.7 Track by GpsGate.....	- 11 -
8. Authorization .....	- 11 -
9. Call Function .....	- 11 -
9.1 Receiving Phone Call .....	- 11 -
9.2 Making Phone Call .....	- 12 -
9.3 Volume Adjustment .....	- 12 -
10. Low Battery Alarm.....	- 12 -
11. Speeding Alarm.....	- 12 -
12. Movement/Geo-fence.....	- 12 -
12.1 Movement Alarm .....	- 12 -
12.2 Geo-fence Alarm .....	- 13 -
13. Listen-in (Voice Monitoring) .....	- 13 -
14. Heartbeat .....	- 14 -
15. Power Down.....	- 14 -
16. Initialization .....	- 14 -
17. Password Initialization.....	- 14 -
18. Parameter Editor .....	- 15 -
19. Copyright and Disclaimer.....	- 15 -
Annex 1. SMS Command List .....	- 15 -
Annex 2. Troubleshooting .....	- 20 -
Contacts.....	- 21 -

## 1.Product Overview

The OCB-GT-06 is a GPS/GPRS based personal tracking device, which is compact and easy to use.

OCB-GT-06 has inbuilt GPS module to obtain accurate position data and utilizes its GSM capability to send the position data to a specified mobile phone or server base to allow users to monitor people or pets using the tracker.

One unique feature of OCB-GT-06 is the inbuilt microphone and loudspeaker that supports two way voice communications like a mobile phone and can be activated either by the guardian calling the tracker or the tracker holder activating the SOS button. The tracker can be configured to report its location to the server base or mobile phone at preset intervals.

OCB-GT-06 has the following functions and features:

- SMS and GPRS TCP/UDP Communication (Nodac Protocol)
- Track on demand
- Show location directly on mobile phone
- Track by time interval
- Two-way audio
- Listen-in (voice monitoring)
- Inbuilt motion sensor for power saving
- SOS panic button
- Movement alarm
- Geo-fencing control
- Low battery alarm
- Speeding alarm
- GPS blind area alarm
- Three buttons for making phone call and/or sending message



## 2.For Your Safety

Read these simple guidelines. Not following them may be dangerous or illegal.

<b>Switch on safely</b>	Do not switch on OCB-GT-06 when wireless phone use is prohibited or when it may
<b>Switch off in hospitals</b>	Follow any restrictions. Switch OCB-GT-06 off near medical equipment.
<b>Switch off in aircraft</b>	Follow any restrictions. Wireless devices can cause interference in aircraft.
<b>Switch off when refueling</b>	Do not use OCB-GT-06 when at a refueling point. Do not use near fuels or
<b>Switch off near blasting</b>	Follow any restrictions. Do not use OCB-GT-06 when blasting is in progress.

**Qualified service**

Only qualified personnel can repair OCB-GT-06.

**Water resistance**

OCB-GT-06 is not fully water resistant. Keep it dry. Use waterproof

necessary.

### 3.OCB-GT-06 Characteristics

Items	Specification
Charging Voltage	DC 4.2-5.5V/400mA (Mini USB port)
Internal Battery	Rechargeable and removable 950 mAh battery (3.7V)
Dimension	78 mm × 45 mm × 21 mm (14mm)
Weight	70g (with battery)
Operating temperature	-20° to 55° C
Humidity	5% to 95% Non-condensing
GSM module	Quad Band GSM 850/900/1800/1900Mhz
GPS Chipset	latest GPS SIRF-Star III chipset
GPS Sensitivity	-158Db
GPS Frequency	L1, 1575.42 MHz
C/A Code	1.023 MHz chip rate
Channels	20 channel all-in-view tracking
Position Accuracy	10 meters, 2D RMS
Velocity Accuracy	0.1 m/s
Time Accuracy	1 us synchronized to GPS time
Default datum	WGS-84
Reacquisition	0.1 sec., average
Hot start	1 sec., average
Warm start	38 sec., average
Cold start	42 sec., average
Altitude Limit	18,000 meters (60,000 feet) max.
Velocity Limit	515 meters/second (1000 knots) max.
Acceleration Limit	Less than 4g
Jerk Limit	20 m/sec
Work time	50 hours in power-saving mode and 10 hours in normal working mode
LED	3 LEDs to show power, GPS, GSM and other status.
Button	3 buttons(SOS/B/C) for making phone calls and sending SMS

### 4.Getting Started

This section will describe how to set up your OCB-GT-06.

#### 4.1 Hardware and Accessories

OCB-GT-06 is supplied in a box which includes:



OCB-GT-06



Battery



Wall Charger



Car Charger



USB Cable



CD

## 4.2 View



Front View



Side View



Back View

## 4.3 Functional Parts

Your OCB-GT-06 has four buttons and three LEDs with three different colors to indicate the status of the unit.



Red LED - indicating battery status	
<b>Off</b>	Power is off or charging is complete
<b>Flashing (every 0.1 second)</b>	Low battery
<b>On</b>	Charging
<b>Flashing (1 second on and 2 seconds off)</b>	Working
Blue LED - indicating GPS status	
<b>On</b>	One button is being pressed
<b>Flashing ( every 0.1 second)</b>	The unit is being initialized
<b>Flashing (0.1 second on and 2.9 seconds off)</b>	OCB-GT-06 has a GPS fix
<b>Flashing (1 second on and 2 seconds off)</b>	OCB-GT-06 has no GPS fix
Green LED - indicating GSM status	

<b>On</b>	One call is coming in / one call is being made
<b>Flashing ( every 0.1 second)</b>	The unit is being initialized
<b>Flashing (0.1 second on and 2.9 seconds off)</b>	OCB-GT-06 is connected to the GSM network
<b>Flashing (1 second on and 2 seconds off)</b>	OCB-GT-06 is not connected to the GSM network
<b>Buttons</b>	
<b>Power On/Off Button</b>	Press and hold it for 3-5 seconds to turn on/off OCB-GT-06
<b>SOS Button</b>	To make a phone call and/or send an SMS to the preauthorized phone number. Press it to receive an incoming call. Press it to increase volume during conversation.
<b>Call B</b>	To make a phone call and/or send an SMS to the preauthorized phone number. Press it to reject a call, cancel calling or complete a conversation.
<b>Call C</b>	To make a phone call and/or send an SMS to the preauthorized phone number. Press it to decrease volume during conversation.
<b>Other Connectors</b>	
<b>Mini USB</b>	Used for charging, firmware update and configuration on PC. (USB Data Cable or USB-to-Serial Adaptor is required for firmware update and configuration)
<b>Lanyard Loop</b>	For connecting lanyard.

#### 4.4 First Use

Please read this manual before using your OCB-GT-06.

4.4.1 Ensure that your OCB-GT-06 has a working SIM installed.

- Check that the SIM has not run out of credit (Test the SIM in a phone to make sure it can send and receive SMS)
- Check that the SIM Lock code is turned off
- If you require the function of sending an SMS location report to the authorized phone number when it makes a call to the OCB-GT-06, please make sure the SIM installed supports displaying caller ID.



4.4.2 Put the battery in OCB-GT-06 and charge the tracker for at least 3 hours in power-off status using the wall charger or car charger. Or you can connect the tracker directly to computer by USB for charging. Red light is on during charging and is off when charging is complete.



4.4.3 Press and hold the Power On/Off button for 3-5 seconds to activate OCB-GT-06 and it will then enter standby mode. It is suggested that you be in an outer place where it can receive better GPS when you turn on the device.





Check that the Red LED (Battery) is flashing 1 second on and 2 seconds off.

Check that the Green LED (GSM) is flashing 0.1 second on and 2.9 seconds off.

Check that the Blue LED (GPS) is flashing 0.1 second on and for 2.9 seconds off.

## 5. Change Password

**Command:** W\*\*\*\*\*,001,#####

**Description:** Change user's password.

**Note:**

1. \*\*\*\*\* is user's password and the default password is 000000. The tracker will only accept commands from a user with the correct password. Commands with wrong password will be ignored.

2. ##### is the new password. Password should be 6 digits.

**Example:**

W000000,001,123456

W123456,001,999999

## 6. Time Zone

**Command:** W\*\*\*\*\*,032,T

**Description:** Correct time into your local time

**Note:**

1. Default time of the tracker is GMT

2. This correction is applied to location reports by SMS and SMS alarms.

T=0, to turn off this function.

T=[-32768,32767] to set time difference in minute to GMT.

For those ahead of GMT, just input the time difference in minute directly. For example, GMT+8,

W000000,032,480

`-` is required for those behind GMT. For example, W000000,032,-120.

**Example:**

W000000,032,480

W000000,032,-120

## 7. Track

### 7.1 Track by SMS

- Track on Demand - Reply with longitude, latitude, speed and date

**Command:** W\*\*\*\*\*,000

**Description:** Get the current location of the tracker, send this SMS or make a telephone call directly to the tracker and it will report its longitude and latitude by SMS with format as follows:-

Latitude = 22 32 36.63N Longitude = 114 04 57.37E, Speed = 2.6854Km/h, 2008-12-24,01:50

**Example:** W000000,000

### - Track on Demand - Reply with a link to Google Map

**Command:** W\*\*\*\*\* ,100



**Description:** Send this command to the tracker and then you receive an SMS with an http link. Click on the link then the location can be shown directly on Google Map on your mobile phone. For example:

<http://maps.google.com/maps?f=q&hl=en&q=22.540103,114.082329&ie=UTF8&z=16&iwloc=addr&om=1>

**Notes:** Only smart phones and PDA support this function.

**Example:**

W000000,100



## 7.2 Track by Calling

Make a missed call to the tracker and it will report its longitude and latitude by SMS with format as follows:-

Latitude = 22 32 36.63N Longitude = 114 04 57.37E, Speed = 2.6854Km/h, 2008-12-24,01:50

## 7.3 Track by Preset Interval

**Command:** W\*\*\*\*\* ,002,XXX

**Description:** Set an interval for the tracker to continuously return its location by SMS

**Note:**

1. XXX is the interval in minute.
2. If XXX=000 to turn off tracking by time

**Example:**

W000000,002,030

The tracker will send location data back to your mobile phone every 30 minutes.

## 7.4 Google Earth and Google Map

Download Google Earth from <http://earth.google.com/>.

Start Google Earth (For more information about Google Earth please refer to <http://earth.google.com/>) or

go to <http://maps.google.com> in your Internet Explorer

Input the latitude and longitude that you receive from the tracker by SMS and click the search button.

Google Earth or Google Maps will display the location for you. Example:


When you receive: Latitude = 22 32 40.05N Longitude = 114 04 57.74E

Turn as the following picture shows:

(Note: you should input the latitude and longitude as: 22 32 40.05N 114 04 57.74E)




And then you can find the location of your tracker:



Or you can use local map software on PDA or car navigation device to input the coordinates.

## 7.5 Track by OCB-GPS-SERVER-01/OCB-GPS-SERVER-02

If you have bought our GPS Tracking Software OCB-GPS-SERVER-01 or OCB-GPS-SERVER-02, after proper configuration, you can do tracking on OCB-GPS-SERVER-01/OCB-GPS-SERVER-02.



Please refer to OCB-GPS-SERVER-01/OCB-GPS-SERVER-02 User Guide for more information.

## 7.6 Track by GPRS (Meiligao Protocol) between Server and Tracker

### 7.6.1 Set Tracker's GPRS ID

**Command:** W\*\*\*\*\*,010,ID

**Description:** Set a digital GPRS ID for the tracker.

**Note:** GPRS ID must not over 14 digits.

**Example:**

W000000,010,00001

### 7.6.2 Set APN

**Command:** W\*\*\*\*\*,011,APN,Username,Password

**Description:** Set APN details for the tracker

**Note:**

1. APN username and password are optional. If no APN username and password are required, just input APN only;
2. APN defaulted as 'CMNET';
3. APN + username + password should not over 39 characters.

**Example:**

W000000,011,CMNET,Meiligao,6688

W000000,011,CMNET

### 7.6.3 Set IP and Port

**Command:** W\*\*\*\*\*,012,IP,Port

**Description:** Set IP and Port for tracker for GPRS communication.

**Note:**

1. IP is your server's IP or the domain name.
2. Port: [1,65534]

**Example:**

W000000,012, 220.121.7.89,8500

W000000,012,www.meiligao.net,8500

### 7.6.4 Set DNS Server IP (optional)

**Command:** W\*\*\*\*\*,009,DNS Server IP

**Description:** In case the domain name you set by the last command (W\*\*\*\*\*,012,IP, Port) doesn't work, which means your server IP is not properly set. You can first use this command to set DNS Server IP (please check with your DNS server provider for the DNS Server IP) and then redo the command W\*\*\*\*\*,012,IP, Port.

**Example:** W000000,009,220.23.4.90

### 7.6.5 Enable GPRS Tracking

**Command:** W\*\*\*\*\*,013,X

**Description:** Enable GPRS tracking function.

**Note:**

- X=0, to turn off GPRS tracking (default);
- X=1, to enable GPRS tracking via TCP
- X=2, to enable GPRS tracking via UDP

**Example:** W000000,013,1

### 7.6.6 Set GPRS Interval

**Command:** W\*\*\*\*\*,014,XXXXX

**Description:** Set time interval for sending GPRS packets.

**Note:**

XXXXX should be in five digits and in unit of 10 seconds.

XXXXX=00000, to turn off this function;

XXXXX=00001~65535, time interval for sending GPRS packet and in unit of 10 seconds.

In this example, the tracker will send every 600 seconds (10 minutes).

**Example:** W000000,014,00060

The tracker will send every 600 seconds (10 minutes).

***For more information regarding GPRS tracking please refer to <GPRS Communication Protocol>***

## **7.7 Track by GpsGate**

The OCB-GT-06 supports GpsGate Software.

Please contact us or GpsGate for more information of settings.

## **8. Authorization**

**Command:** W\*\*\*\*\*,003,F,P,T1 or W\*\*\*\*\*,003,F,P,T1,T2 (optional)

**Description:** Authorize phone numbers for the buttons/inputs for receiving location reports or SMS alarms or phone calls

**Note:**

F=0, to turn off this function; (default)

F=1, only sends SMS to the authorized phone number;

F=2, only calls the authorized phone number;

F=3, both SMS and calling.

P=1, set an authorized number for SOS button (Input 1);

P=2, set an authorized number for B button (Input 2);

P=3, set an authorized number for C button (Input 3).

T1: Preset phone number. Max.16 digits.

If you need to set different numbers for receiving SMS and phone call, you can then use W\*\*\*\*\*,003,F,P,T1,T2, In this case T1 is the phone number for receiving SMS and T2 for receiving phone call.

**Example:**

W000000,003,3,1,88888888

W000000,003,3,1,88888888,99999999

## **9. Call Function**

Based on OCB-GT-06's inbuilt loudspeaker and microphone, you can use OCB-GT-06 to make or receive phone calls.

### **9.1 Receiving Phone Call**

Use your phone or mobile phone to call the tracker, the green LED will be on and you hear beeps produced by the tracker. Press SOS button to receive the incoming call or press Call B button to reject the call.

## 9.2 Making Phone Call

After you have authorized phone numbers for SOS/Call B/Call C button, you can press one of these buttons to make a call to the preset phone number.

Press Call B button to cancel a calling or to end a conversation.

## 9.3 Volume Adjustment

During a conversation, press SOS button to increase the volume or press Call C button to decrease the volume.

## 10. Low Battery Alarm

**Command:** W\*\*\*\*\*,004,X

**Description:** When the tracker's voltage is lower than the preset value, it will send an SMS alarm to the authorized phone number for SOS.

**Note:**

X is the preset value of voltage.

=0 , to turn off this function	=1, <3.3V	=2 , <3.4V
=3 , <3.5V (default)	=4 , <3.6V	=5 , <3.7V

**Example:** W000000,004,2

## 11. Speeding Alarm

**Command:** W\*\*\*\*\*,005,XX

**Description:** Turn on speeding alarm. When the tracker speeds higher than the preset value, it will send an SMS to the phone number for SOS.

**Note:**

XX is the preset value of speed and in 2 digits.

=00 , to turn off this function

= [01, 20] (unit: 10Km/h)

**Example:** W000000,005,08

When the tracker's speed is over 80km/h, an SMS alarm will be sent out.

## 12. Movement/Geo-fence

### 12.1 Movement Alarm


**Command:** W\*\*\*\*\*,006,XX

**Description:** When the tracker moves out of a preset square scope, it will send an SMS alarm to the authorized phone number for SOS.

**Note:** XX is the preset distance to the tracker's original place =00, to turn off this function

=01, 30m	=02, 50m	=03, 100m	=04, 200m
=05, 300m	=06, 500m	=07, 1000m	=08, 2000m

**Example:** W000000,006,06



When tracker moves out of this square scope, it will send out an SMS alarm.

## 12.2 Geo-fence Alarm

**Command:** W\*\*\*\*\*,017,X or W\*\*\*\*\*,117,X

**Description:** Turn on Geo-fencing alarm. When the tracker moves in/out the preset scope, it will send an SMS alarm to the authorized phone number for SOS.

**Note:**

1. 017 is for alarm when tracker moves out the preset scope;
2. 117 is for alarm when tracker moves in.
3. X is the coordinates which include: Lower-left X,Lower-left Y,Upper-right X,Upper-right Y
4. Lower-left X should be less than Upper-right X;
5. All longitudes and latitudes should be in ASCII format as follows:-  
 Longitude: DDDMM.MMMM,E/W. 4 places of decimal. '0' is needed to be stuffed if no value available.  
 Latitude: DDMM.MMMM,N/S. 4 places of decimal. '0' is needed to be stuffed if no value available;
6. Send W\*\*\*\*\*,006,00 to turn off Geo-fence function.

**Example:**

W000000,017,11404.0000,E,2232.0010,N,11505.1234,E,2333.5678,N

W000000,117,11404.0000,E,2232.0010,N,11505.1234,E,2333.5678,N

**Remarks:**

1. Only one alarm can be set in either In or Out;
2. Only one alarm can be set in either Movement Alarm or Geo-fence Alarm.

## 13. Listen-in (Voice Monitoring)

**Command:** W\*\*\*\*\*,030,T

**Description:** Authorize a phone number to make a silence call to the tracker, the track answers the call automatically and allows the caller to listen to what happens around the tracker. There is no voice indication that the call is in progress

**Note:**

1. T is the telephone number for wiretapping and max. 16 digits
2. Calls from unauthorized number are treated as normal incoming calls and indicated by beeps.

**Example:**

## 14. Heartbeat

**Command:** W\*\*\*\*\*,015,data

**Description:** Set an interval for heartbeat.

**Note:**

data is the interval in unit of minute

data=0, to turn off this function;

data=1~65535, set interval for heartbeat.

**Example:**

W000000,015,10

In this example, the tracker will send heartbeat every 10 minutes.

## 15. Power Down

**Command:** W\*\*\*\*\*,026,XX

**Description:** Make the tracker into power down mode when it is inactive or immobile for a period of time. In Power Down states, GPS stops working and GSM enters sleep and stop sending out message until it is activated by message, incoming calls or movement or triggered by three buttons.

**Note:**

XX=00, to turn off this function.

XX=01~99, to turn on Power Down after a specified period of being inactive (or stationary). It is in unit of minute.

**Example:** W000000,026,10

The tracker will enter power down mode after it is inactive (or stationary) for 10 minutes.

## 16. Initialization

**Command:** W\*\*\*\*\*,990,099###

**Description:** This is to make all settings (except for the password) back to factory default.

**Note:** Turn on the device, press the SOS button for five times continuously and the red LED will be on, and then send (within 120 seconds) this SMS to the tracker.

### is the ending character and is required in the text message.

**Example:** W000000,990,099###

## 17. Password Initialization

**Command:** W888888,999,666

**Description:** This is to make the password back to factory default in case you forget your password.

**Notes:** Turn on the tracker, press the SOS button for five times continuously and the red LED will be on, and then send this SMS (within 120 seconds) to the tracker to make the password back to factory default

(000000).

**Example:** W888888,999,666

**For more details regarding SMS commands, please go to Annex 1 Command List.**

### 18. Parameter Editor

The tracker can be configured by computer using the Parameter Editor.



GPS Tracker Parameter Editor V1.39

Please refer to <GPS Tracker Parameter Editor> for more information.

### 19. Copyright and Disclaimer

© Shenzhen Meiligao Electronics Co., Ltd. All rights reserved.

The information contained herein may be changed at any time without prior notification. This manual nor any parts thereof may not be reproduced for any purpose whatsoever without the express written consent of Meiligao, nor transmitted in any form either electronically or mechanically, including photocopying and recording.

In no event shall Meiligao be liable for direct, indirect, special, incidental, or consequential damages (including but not limited to economic loss, such as loss of profits, loss of use of profits, loss of business or business interruption, loss of revenue, loss of goodwill or loss of anticipated savings) arising out of the use or inability to use the product or documentation, even if advised of the possibility of such damages.

### Annex 1. SMS Command List

Note: \*\*\*\*\* is user's password and the default password is 000000. The tracker will only accept commands from a user with the correct password. Commands with wrong password will be ignored.

Description	SMS Command	Example
<b>Track on Demand</b>	W*****,000	W000000,000
Remarks: To get the current location of the tracker, send this SMS or make a telephone call directly to the tracker and it will report its longitude and latitude by SMS with format as follows:-		
Latitude = 22 32 36.63N Longitude = 114 04 57.37E, Speed = 2.6854Km/h, 2008-12-24,01:50		

<b>-Google Link</b>								
<p>Remarks: Send this command to the tracker and then you receive an SMS with an http link. Click on the link then the location can be shown directly on Google Map on your mobile phone. For example:</p> <p><a href="http://maps.google.com/maps?f=q&amp;hl=en&amp;q=22.540103,114.082329&amp;ie=UTF8&amp;z=16&amp;iwloc=addr&amp;om=1">http://maps.google.com/maps?f=q&amp;hl=en&amp;q=22.540103,114.082329&amp;ie=UTF8&amp;z=16&amp;iwloc=addr&amp;om=1</a></p> <p>(Note: Only smart phones and PDA support this function.)</p>								
<b>Change Password</b>	W*****,001,#####	W000000,001,123456						
<p>Remarks: To change user's password. ##### is the new password. Password should be 6 digits.</p>								
<b>Track by Interval</b>	W*****,002,XXX	W000000,002,030						
<p>Remarks: To set interval for automatic timed report.</p> <p>XXX is the interval in minute. If XXX=000 to turn off tracking by time.</p> <p>In this example, the tracker will send location data back to your mobile phone every 30 minutes.</p>								
<b>Authorization</b>	W*****,003,F,P,T1 (W*****,003,F,P,T1,T2)	W000000,003,3,1,88888888 W000000,003,3,1,88888888,99999999						
<p>Remarks: To authorize phone numbers for the buttons/inputs for receiving location reports or SMS alarms or phone calls.</p> <p>F=0, to turn off this function; (default)</p> <p>F=1, only send SMS to the authorized phone number;</p> <p>F=2, only call the authorized phone number;</p> <p>F=3, both SMS and calling</p> <p>P=1, set an authorized number for SOS button (Input 1)</p> <p>P=2, set an authorized number for B button (Input 2)</p> <p>P=3, set an authorized number for C button (Input 3)</p> <p>T1: Preset phone number. Max.16 digits</p> <p>If you need to set different numbers for receiving SMS and phone call, you can then use W*****,003,F,P,T1,T2, In this case T1 is the phone number for receiving SMS and T2 for receiving phone call.</p>								
<b>Low Battery Alarm</b>	W*****,004,X	W000000,004,2						
<p>Remarks: When the tracker's voltage is lower than the preset value, it will send an SMS alarm to the authorized phone number for SOS.</p> <p>X is the preset value of voltage.</p> <table border="1" data-bbox="219 1507 1258 1591"> <tr> <td>=0 , to turn off this function</td> <td>=1, &lt;3.3V</td> <td>=2 , &lt;3.4V</td> </tr> <tr> <td>=3 , &lt;3.5V (default)</td> <td>=4 , &lt;3.6V</td> <td>=5 , &lt;3.7V</td> </tr> </table>			=0 , to turn off this function	=1, <3.3V	=2 , <3.4V	=3 , <3.5V (default)	=4 , <3.6V	=5 , <3.7V
=0 , to turn off this function	=1, <3.3V	=2 , <3.4V						
=3 , <3.5V (default)	=4 , <3.6V	=5 , <3.7V						
<b>Speeding Alarm</b>	W*****,005,XX	W000000,005,08						
<p>Remarks: When the tracker speeds higher than the preset value, it will send an SMS to the authorized phone number for SOS.</p> <p>XX is the preset value of speed and in 2 digits.</p> <p>=00 , to turn off this function</p> <p>=[01, 20] (unit: 10Km/h)</p> <p>In this example, when the tracker's speed is over 80km/h, an SMS alarm will be sent out.</p>								
<b>Movement Alarm</b>	W*****,006,XX	W000000,006,06						

Remarks: When the tracker moves out of a preset square scope, it will send an SMS alarm to the authorized phone number for SOS.

XX is the preset distance to the tracker's original place

=00, to turn off this function

=01, 30m	=02, 50m	=03, 100m	=04, 200m
=05, 300m	=06, 500m	=07, 1000m	=08, 2000m

<b>Geo-fence Alarm</b>	W*****,017,X	W000000,017,11404.0000,E,2232.0010,N,11505.1234,E,2333.5678,N
	W*****,117,X	W000000,117,11404.0000,E,2232.0010,N,11505.1234,E,2333.5678,N

Remarks: 017 is for alarm when tracker moves out the preset scope; 117 is for alarm when tracker moves in.

When the tracker moves in or out, it will send an SMS alarm to the authorized phone number for SOS.

X is the coordinates which include:

Lower-left X, Lower-left Y, Upper-right X, Upper-right Y

For example, 11404.0000,E,2232.0010,N,11505.1234,E,2333.5678,N

Note:

1. Lower-left X should be less than Upper-right X;
2. All longitudes and latitudes should be in ASCII format as follows:-  
Longitude: DDDMM.MMMM,E/W. 4 places of decimal. '0' is needed to be stuffed if no value available.  
Latitude: DDMM.MMMM,N/S. 4 places of decimal. '0' is needed to be stuffed if no value available;
3. Only one alarm can be set in either Movement Alarm or Geo-fence Alarm;
4. Send W\*\*\*\*\*,006,00 to turn off Geo-fence function.

<b>Extended Functions</b>	W*****,008,ABCDEFHIJ## #	W000000,008,1011100011###
---------------------------	-----------------------------	---------------------------

Remarks:

**A=0**, turn off the function of sending SMS location report after a phone call is made to the tracker.

**A=1**, turn on the function of sending SMS location report after a phone call is made to the tracker.

**B=0**, location data of NMEA 0183 GPRMC will be interpreted into normal text for easy reading.

For example, Latitude = 22 32 36.63N Longitude = 114 04 57.37E, Speed = 2.6854Km/h, 2008-12-24,01:50

**B=1**, location data complies with NMEA 0183 GPRMC protocol.

For example, \$GPRMC,161509.000,A,2232.5485,N,11404.6887,E,0.3,153.7,290709,,\*03

**C=0**, turn off the function to automatically hang up an incoming call.

**C=1**, turn on the function to automatically hang up an incoming call after 4 - 5 rings.

**D=0**, turn off the function of sending an SMS when the tracker is turned on.

**D=1**, turn on the function of sending an SMS to the authorized phone number for SOS when the tracker is turned on.

**E**, defaulted as 1 (the tracker shuts down automatically when the power voltage is lower than 3V).

**F=0**, turn off the SMS alarm when the tracker enters GPS blind area.

**F=1**, turn on the SMS alarm when the tracker enters GPS blind area. SMS is to be sent to the authorized phone number for SOS.

**G=0**, 3 LEDs work normally.

**G=1**, 3 LEDs stop flashing when the tracker is working.

**I**, reserved and defaulted as '0'

**J=0**, turn off the buzzer for the incoming call.

**J=1**, turn on the buzzer for the incoming call.

**###** is the ending character

(ABCDEFGHIJ defaulted as 1000100001)

**Presetting by SMS for GPRS tracking (Ensure that your SIM card supports GPRS connection prior to setting)**

<b>Set Tracker's GPRS ID</b>	W*****,010,ID	W000000,010,00001
------------------------------	---------------	-------------------

Remarks: to set a digital GPRS ID for the tracker.

GPRS ID must not over 14 digits.

<b>Set APN</b>	W*****,011,APN,Username,	W000000,011,CMNET,Meiligao,6688
	Password	W000000,011,CMNET

Remarks: If no APN username and password are required, just input APN only;

APN defaulted as 'CMNET';

APN + username + password should not over 39 characters.

<b>Set IP and Port</b>	W*****,012,IP,Port	W000000,012, 220.121.7.89,8500
		W000000,012,www.meiligao.net,8500

Remarks: IP is your server's IP or the domain name. Port: [1,65534]

<b>Set DNS Server IP</b>	W*****,009,DNS Server IP	W000000,009,220.23.4.90
--------------------------	--------------------------	-------------------------

Remarks: In case the domain name you set by the last command (W\*\*\*\*\*,012,IP, Port) doesn't work, which means your server IP is not properly set. You can first use this command to set DNS Server IP (please check with your DNS server provider for the DNS Server IP) and then redo the command W\*\*\*\*\*,012,IP,Port.

<b>Enable GPRS Tracking</b>	W*****,013,X	W000000,013,1
-----------------------------	--------------	---------------

Remarks:

X=0, to turn off GPRS tracking (default);

X=1, to enable GPRS tracking via TCP

X=2, to enable GPRS tracking via UDP

<b>Set GPRS Interval</b>	W*****,014,XXXXX	W000000,014,00060
--------------------------	------------------	-------------------

Remarks: to set time interval for sending GPRS packets.

XXXXX should be in five digits and in unit of 10 seconds.

XXXXX=00000, to turn off this function;

XXXXX=00001~65535, time interval for sending GPRS packet and in unit of 10 seconds.

In this example, the tracker will send every 600 seconds (10 minutes).

<b>Set Heartbeat Interval</b>	W*****,015,data	W000000,015,10
-------------------------------	-----------------	----------------

Remarks: to set interval for heartbeat.

Data: in unit of minute

data=0, to turn off this function;

data=1~65535, set interval for heartbeat.

In this example, the tracker will send heartbeat every 10 minutes.

**Heading Change Report**

W\*\*\*\*\*,036,degree

W000000,036,90

Remarks: when the heading direction of the tracker changes over the preset degree, a message with location data will be sent back to the server by GPRS.

degree=0, to turn off this function.

degree=[1,360], to set degree of direction change.

**For more information regarding GPRS tracking please refer to <GPRS Communication Protocol>**

**Sleep Mode**

W\*\*\*\*\*,021,XX###

W000000,021,02###

Remarks: this setting is for power saving.

XX=00 turn off sleep mode

XX=01 Level I

XX=02 Level II

### is the ending character

Here is some explanation for the sleep mode. First, assume that the GPS acquisition time is ONE minute.

[1] In Level I

The GPS module will be working for the first three minutes (i.e. 3 times of acquisition time) and then shut down for ONE minute (i.e. equivalent to acquisition time), and then work again for another three minutes.....

[2] In Level II

The GPS module will be working for the first two minutes (i.e. twice of acquisition time) and then shut down for ONE minute (i.e. equivalent to acquisition time), and then work again for another two minutes.....

**Power Down**

W\*\*\*\*\*,026,XX

W000000,026,10

Remarks: to set power down mode when the tracker is inactive or stationary for a period of time.

In Power Down mode, GPS stops working and GSM enters sleep and stop sending out message until it is activated by message , incoming calls, movement or triggered by three buttons

XX=00, to turn off this function.

XX=01~99, to turn on Power Down after a specified period of being inactive (or stationary). It is in unit of minute.

In this example, the tracker will enter power down mode after it is inactive (or stationary) for 10 minutes.

**Listen-in (Voice Monitoring)**

W\*\*\*\*\*,030,T

W000000,030,88888888

Remarks: T is the telephone number for wiretapping and max. 16 digits

**Time Zone**

W\*\*\*\*\*,032,T

W000000,032,480 W000000,032,-120

Remarks: Default time of the tracker is GMT. You can use this comment to correct it to your local time. This command is for SMS tracking only.

T=0, to turn off this function.

T=[-32768,32767] to set time difference in minute to GMT.

For those ahead of GMT, just input the time difference in minute directly. For example, GMT+8, W000000,032,480

`-`is required for those behind GMT. For example, W000000,032,-120.

**Set SMS Header**

W\*\*\*\*\*,033,P,Char

W000000,033,1,help

Remarks: this command is to set initial characters for SOS message when SOS/IN1, Button B/IN2, Button C/IN3 is pressed. P=1, SOS button/Input1                      P=2, B button/Input2                      P=3, C button/Input3 Char is the character in SOS message and max 32 characters and defaulted as:		
1 SOS Alarm!	2 Cry For Help!	3 Call The Police!
<b>Set Prefix (Country Code)</b>	W*****,502,*Data#	W000000,502,*+86#
Remarks: be advised caution in this setting. Normally, your country code (for example in China it is +86) will be automatically added and displayed prior to a phone number when sending SMS. In this case, you don't have to do this setting. If the country code is not added, you are required to input the country code, for example, +86, to enable the tracker can send out SMS to your mobile phone. Data: max 10 digits		
<b>Get Version No. and Serial No.</b>	W*****,600	W000000,600
Remarks: to get the version and serial number of tracker's firmware		
<b>Get IMEI</b>	W*****,601	W000000,601
Remarks: to get IMEI of the tracker		
<b>Reboot GSM</b>	W*****,901###	W000000,901###
Remarks: to reboot the GSM module of the tracker		
<b>Reboot GPS</b>	W*****,902###	W000000,902###
Remarks: to reboot the GPS module of the tracker		
<b>Initialization</b>	W*****,990,099###	W000000,990,099###
Remarks: Turn on the device, press the SOS button for five times continuously and the red LED will be on, and then send (within 120 seconds) this SMS to the tracker to make all settings (except for the password) back to factory default. ### is the ending character.		
<b>Password Initialization</b>	W888888,999,666	W888888,999,666
Remarks: In case you forget your password, turn on the tracker, press the SOS button for five times continuously and the red LED will be on, and then send this SMS (within 120 seconds) to the tracker to make the password back to factory default (000000).		

## Annex 2. Troubleshooting

<b>Problem: Unit will not turn on</b>	
<b>Possible Cause:</b>	<b>Resolution:</b>
The power button is not pressed long enough	Press and hold the button for 3-5 seconds.
Battery needs charging	Recharge battery for 3 hours
<b>Problem: Unit will not reply with SMS</b>	

<b>Possible Cause:</b>	<b>Resolution:</b>
Green LED is flashing (1 second on and 2 seconds off)	Make OCB-GT-06 connected to GSM network.
GSM Network is slow	Some GSM networks slow down during peak time or when they have equipment problems.
Unit is sleeping or in power down mode	Cancel sleeping mode or power down
Wrong password in your SMS or wrong SMS format	Write correct password or SMS format
The SIM in OCB-GT-06 has run out of credit	Replace or top up the SIM card
<b>Problem: Green LED is Flashing (1 second on and 2 seconds off)</b>	
<b>Possible Cause:</b>	<b>Resolution:</b>
No GSM signal	Check with a mobile phone to see if there is a signal in the area or try to call the unit to see if you hear a ring tone.
No SIM card	Insert a working SIM card. Check in phone that the SIM can send SMS message.
SIM card has expired	Check in phone that the SIM can send SMS message. Replace SIM card if needed.
SIM has PIN code set	Remove PIN code by inserting SIM in you phone and deleting the code.
SIM is warped or damaged	Inspect SIM, clean the contacts. If re-inserting does not help try another to see if it will work.
Roaming not enabled	If you are in a different country your SIM account must have roaming enabled.
Battery is low	Recharge the unit and the GSM will start working.
<b>Problem: Blue LED is Flashing (1 second on and 2 seconds off) or the SMS received starts with 'Last...'</b>	
<b>Possible Cause:</b>	<b>Resolution:</b>
Unit does not have clear view of the sky	Move the unit to a location where the sky is visible. Tall buildings, trees, heavy rain, can cause problems with the GPS reception.
Bad GPS reception	Place the front side of OCB-GT-06 towards sky
Battery is low	Recharge the unit and the GPS will start working.
<b>Problem: Unit Fails to Connect to Server via GPRS</b>	
<b>Possible Cause:</b>	<b>Resolution:</b>
SIM card in OCB-GT-06 does not support GPRS function	Enable SIM card GPRS function.
GPRS function of OCB-GT-06 is turned off	Turn on GPRS function of OCB-GT-06.
Incorrect IP address or PORT	Get the right IP address and PORT and reset to OCB-GT-06.
GSM signal is weak	Move the unit to a location with good GSM reception.

## Contacts

If you encounter any problems when using our products, and cannot solve them by yourself, please contact our technical support team by writing an E-Mail to [info@nodactechnology.com](mailto:info@nodactechnology.com). We will be pleased to help you.